




## APPLICATION TECHNIQUES - For Professional Use Only



### DESCRIPTION

ALCO Non-Fibered Asphalt Emulsion Roof Coating consists of a specially formulated asphalt and an emulsifying agent. It can be applied to most horizontal and vertical surfaces without sagging. Being a water based material, it is non-flammable and will not support combustion.

### USE

Inexpensive protective coating for BUR, metal or roll roofing.

### ADVANTAGES

- Easy application – Spray or Brush
- Ready to use from the container
- Capable of bonding on damp surfaces (not wet)
- No heating or thinning
- Fast and economical way to coat roof deck



### Full ALCO Warranty

Ask your sales representative or visit our Web site for complete details.



Made in USA

*ALCO Products offer installers a complete line of professional roof protection products.*

Your Second Line of Defense™

800.323.0029 | [www.alco-products.com](http://www.alco-products.com)

## PREPARATION

Roof surface and all parapets should be swept clean of all dust and dirt. All repairs must be made before coating, using a cotton or fiberglass membrane or ALCO Poly-S, in conjunction with a quality roof cement such as ALCO Plastic Roof Cement, ALCO Wet-Bond Cement or ALCO 24/7 Flashing Cement.

A primer, such as ALCO Concrete and Roof Primer should be used under emulsion roof coating. If a primer coat is not used, surface to be coated should be thoroughly hosed down with a high pressure hose and scrubbed with a stiff broom.

## APPLICATION

Stir material to even consistency and color.

For best results, apply when the temperature is 50° F. and rising and with no chance of rain within 24 hours. Allow 4 – 8 hours drying time and 2 days for effective cure.

**BRUSH:** Apply with soft bristle brush. Pour material directly from the container and brush to a smooth and even coat.

**SPRAY:** Use a standard type mastic pump.

## APPROXIMATE COVERAGE

Brush Application	40 – 50 SF/Gallon
Spray Application	40 – 50 SF/Gallon

## SPECIFICATION

ASTM D-1227, Type III, Class 1

## PACKAGING

4.75 Gallon Pail	36/Pallet
------------------	-----------

## LIMITATIONS

- PROTECT FROM FREEZING
- For outdoor use only
- For professional use only
- Do not thin this material
- Do not use on wood
- If winter storage is necessary, maintain temperature above 50° F. and keep material off floor.
- Secure cover when not in use

## PROPERTIES

Weight per Gallon (Approximate):	8.3 Lbs
Percent Non-Volatile (Fed Test Method 141):	50% +
Percent of Asphalt:	45% +
Percent of Total Solids, by Volume:	53% +
Viscosity:	10,000 – 15,000 cps
Ash on Basis of Non-Volatile Material:	5% +
Penetration of Base Asphalt (ASTM D-5):	85 – 100
Flash Point of Base Asphalt, C.O.C. F:	450 +
Ductility of Base Asphalt:	100 +
Film Thickness of 1 GAL/50 SF: (less absorption by surface)	1/32"

FOR FURTHER SAFETY INFORMATION SEE MSDS REGARDING THIS PRODUCT

## PRECAUTIONS

**Caution:** Contains Petroleum Hydrocarbons

**Hazard Rating:** Health – 1 Fire – 0 Reactivity – 0  
(0 = Least; 4 = Extreme)

**Personal Protection:** Avoid prolonged or repeated contact with skin, which may cause irritation. Wear chemical resistant gloves. Do not get in eyes; wear protective goggles or face shield. Wear protective clothing if needed. Do not take internally.

**Fire Protection:** Non-flammable

## First Aid

**Eye Contact** – Rinse immediately with water for 15 minutes and seek medical advice.

**Skin Contact** – Wash with a waterless hand cleaner and/or soap and water.

**Ingestion** – Do not induce vomiting. Get medical attention immediately.

**Waste Disposal** – Seal container when not in use. Empty containers must be disposed in an approved landfill in accordance with local, state and Federal regulations.

**KEEP OUT OF REACH OF CHILDREN!**