

Available in .9-gallon,
2.75-gallon and 4.75-gallon cans



APPLICATION TECHNIQUES
For Professional Use Only



DESCRIPTION

ALCO Wet-Bond Plastic Roof Cement is a special blend of refined cutback asphalt, a special chemical bonder and fiber fillers. It is of heavy trowel consistency and can be applied to wet or dry surfaces.

USE

- Emergency repair of wet or damp roof surfaces

ADVANTAGES

- Adheres to wet surfaces
- Easy application
- Ready to use from the container
- Excellent adhesion to many common roof surfaces
- Produced in Summer, Spring/Fall and Winter Grades



Full ALCO Warranty

Ask your sales representative or visit our Web site for complete details.



Made in USA

ALCO Products offer installers a complete line of professional roof protection products.

Your Second Line of Defense™

800.323.0029 | www.alco-products.com

PREPARATION

Before application, be sure area to be repaired is free from dirt, grease, oil and debris. Be sure that all standing water, ice and snow are swept away from repair area. A cloth membrane may be needed to repair larger cracks.

APPLICATION

Apply with a trowel or putty knife. On small hairline cracks, fill the cracks and feather down all edges. On larger cracks or voids it may be necessary to use a membrane cloth. Apply material at approximately 1/4" thickness, imbedding the membrane directly into the cement and making sure to feather down all edges. Once repair has been completed, coat the entire surface with ALCO Wet-Bond Fiber Coating.

For ease of application in cold weather, keep material at room temperature before use.

When applying this material during inclement weather, it is advisable to inspect the job when better working conditions return.

APPROXIMATE COVERAGE

1/8" Film	12.5 SF/Gallon
1/4" Film	6.25 SF/Gallon

SPECIFICATION

ASTM D-4586, Type I

VOC

Not to Exceed: 300 g/L 2.5 Lbs/Gal

FOR OUTDOOR USE ONLY
DO NOT THIN THIS PRODUCT
SECURE COVER WHEN NOT IN USE

PACKAGING

.9 Gallon Can	6/Carton
2.75 Gallon Pail	60/Pallet
4.75 Gallon Pail	36/Pallet

LIMITATIONS

- Not for use on wood
- For professional use only
- Not compatible with roofs previously coated with Coal Tar
- May not be compatible with some roof systems. Check with the manufacturer of roof system before application.

PROPERTIES

Flash Point (ASTM D-93):	100° F. +
Weight per Gallon (Approximate):	8.5 Lbs
Non-Volatile (Fed Test Method 141):	70% +
Percent of Specially Processed Asphalt:	35% to 65%
Mineral and/or Other Stabilizers:	15% - 40%
Percent of Total Solids, by Volume:	65% +
Film Thickness of 1 GAL/12.5 SF:	1/8"
Drying Time:	2 – 3 Days
Service Temperature, Extended Exposure:	-40° to 150° F.
Resistance to Oils & Solvents:	Poor
Resistance to Sunlight:	Excellent
Resistance to Chemicals:	Good
Effect of Weathering:	Slight Chalking
Resistance to Water:	
Under Good Drainage Conditions:	Excellent
Under Continuous Submersion:	Not Recommended

FOR FURTHER SAFETY INFORMATION SEE MSDS REGARDING THIS PRODUCT

PRECAUTIONS

Caution Combustible - Contains Petroleum Distillates

Hazard Rating: Health – 1 Fire – 2 Reactivity – 0
(0 = Least; 4 = Extreme)

Respiratory: Use with adequate ventilation. Inhalation of high vapor concentration may cause headaches and/or dizziness. NIOSH/MSHA Respirators required if TLV is exceeded.

Personal Protection: Avoid prolonged or repeated contact with skin, which may cause irritation. Wear chemical resistant gloves. Do not get in eyes; wear protective goggles. Wear protective clothing if needed. Do not take internally.

Fire Protection: Keep away from heat, open flame and any source of ignition.

FIRST AID

Eye Contact – Rinse immediately with water for 15 minutes and seek medical advice.

Skin Contact – Wash thoroughly with soap and water.

Inhalation – Remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration; get medical attention and keep victim warm.

Ingestion – Do not induce vomiting. Get medical attention immediately.

Waste Disposal – Seal container when not in use. Empty containers must be disposed in an approved landfill in accordance with local, state and Federal regulations.

KEEP OUT OF REACH OF CHILDREN!