



Residential



Commercial



ALCO 24/7 Roof Repair Tape

The revolutionary Leak and Seam Repair Tape for TPO, EPDM, Metal, Modified Bitumen and B.U.R. systems with Ultra Aggressive Sealability.

ALCO 24/7 Roof Repair Tape is the most aggressive sealing tape available. Highly effective, long-term solution for repairing leaks on virtually all roofing materials, including TPO, EPDM, and metal.

ALCO 24/7 Roof Repair Tape is also extremely effective in below grade concrete wall penetrations for water, sewer and electrical service.

Features & Benefits

- Perfect for reinforcing non-leaking seams and for additional security around curbs, vents, chimneys, AC systems, antennas, or any roof-penetrating devices
- VOC-free and stable from -70° F to 200° F
- Easy to apply to clean, dry surfaces
- Flexible and readily conforms to shapes - making it well suited for gutter repairs, piping and other curved equipment
- UV Resistant for assured longevity - available in two backing colors - white and black.
- Ultra Aggressive Sealing properties means it can be effectively used to stop water or air penetration on many other surfaces, including cement, plywood, OSB, and metal.
- Excellent for stopping leaks on mobile homes, RVs, vans, garden sheds, tarpaulins and some unpressurized piping.

Full ALCO Warranty



Ask your sales representative or visit our **Web site** for complete details.

ALCO Products offer installers a complete line of roof protection products.

Your Second Line of Defense™

800.323.0029 | www.alco-products.com



Application Instructions


- Measure area of the leak you want to apply repair tape.
- Make sure the area to be repaired is clean and dry.
- Remove loose material.
- If there are any oil-based residues, remove them with the appropriate cleaners.
- Cut the required length of ALCO 24/7 Roof Repair Tape and remove release coating from the inward-facing of the tape.
- Press into place by hand.
- Roll with a hand roller to force adhesive into any surface irregularities.



MEASURE




CLEAN



CUT & PEEL



APPLY



ROLL

IMPORTANT: ALCO 24/7 Roof Repair Tape cannot be removed by hand from ANY surface to which it is applied. Removal of this material requires mechanical intervention or high-strength solvents. **DO NOT** apply our repair tape to any surface with the expectation that it will be readily removed without affecting the surface to which it is applied.

Technical Data

Property	Test Method	Typical Value
Thickness w/o liner	ASTM D1777	26 mils
Tensile Strength	ASTM D882	15 lb _f /in
Elongation	ASTM D882	> 700%
Adhesion	PSTC-1	20 lb _f /in
25° F Peel adhesion	ASTM D6862	13 lb _f /in
150° F Peel adhesion	ASTM D6862	2.2 lb _f /in
WVTR @ 73° F/50%rh	ASTM E96-B	< 0.02 g / 100in ² /24hr
Permeance @ 73° F/50%rh	ASTM E96-B	< 0.05 perms
Low Temperature Flexibility	ASTM D1970	Excellent
Application Temperature		20° F to 170° F
w/recommended Primer		-25° F to 25° F
Service Temperature		-70° F to 200° F
Shelf Life		5 years

Product Information

Standard Roll Sizes	4 inch, 6 inch, and 12 inch x 25 feet
Case Quantity	12 rolls, 8 rolls, and 4 rolls
Available Colors	White and Black

Ultra Agressive Sealing properties means it can also be effectively used to stop water or air penetration on...



Plywood, and OSB



Recreation Vehicles and Trailer Roofs



Metal, Gutters & More