



## DIRECTIONS FOR USE

1. Spray full strength to a dry surface.
2. For hard surfaces, let stand on surface until spot or stain appears loosened, then rinse with water to remove residue.
3. For fabrics, wet fabric with Asphalt & Tar Remover, rub into stain and wash article in washing machine.
4. On carpeting, apply sparingly and blot stain lightly; blot again with clean cloth. Repeat as necessary, then rinse with water.

## PACKAGING

Quart Containers      12/Carton

FOR FURTHER SAFETY INFORMATION SEE MSDS REGARDING THIS PRODUCT

## PRECAUTIONS

**Caution** Combustible - Contains Petroleum Distillates

**Hazard Rating:** Health – 1    Fire – 2    Reactivity – 0  
(0 = Least; 4 = Extreme)

**Respiratory:** Use with adequate ventilation. Inhalation of high vapor concentration may cause headaches and/or dizziness. NIOSH/MSHA Respirators required if TLV is exceeded.

**Personal Protection:** Avoid prolonged or repeated contact with skin, which may cause irritation. Wear chemical resistant gloves. Do not get in eyes; wear protective goggles. Wear protective clothing if needed. Do not take internally.

**Fire Protection:** Keep away from heat, open flame and any source of ignition.

## FIRST AID

**Eye Contact** – Rinse immediately with water for 15 minutes and seek medical advice.

**Skin Contact** – Wash thoroughly with soap and water.

**Inhalation** – Remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration; get medical attention and keep victim warm.

**Ingestion** – Do not induce vomiting. Get medical attention immediately.

**Waste Disposal** – Seal container when not in use. Empty containers must be disposed in an approved landfill in accordance with local, state and Federal regulations.

**KEEP OUT OF REACH OF CHILDREN!**