

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Alco Asphalt Roof Primer
CAS No : 8052-42-4
Product code : 207
Synonyms : asphalt / asphalt blending stocks: straight run residue / asphalt, not cut back / asphalt, petroleum / asphalt, straight reduced / asphalt, straight run / asphalt, syriac / bitumen / bitumes, hot / carpeting medium / compact bitumen / earth pitch / Elevated temperature liquid, n.o.s. / Elevated temperature liquid, n.o.s., at or above 100 °C and below its flashpoint (including molten metals, molten salts, etc.), filled at a temperature higher than 190 °C / judean pitch / mineral pitch / petroleum asphalt / petroleum pitch / petroleum residue, asphalt / petroleum roofing tar / pitch, judean / residual asphalt / road asphalt / road binder / road tar / seal-coating material

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use
Coating: component

1.3. Details of the supplier of the safety data sheet

ALCO PRODUCTS, LLC
580 St. Jean
Detroit, MI 48214
T (313) 823-7500 - F (313) 331-4726
info@alco-products.com - www.alco-products.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 CHEMTREC

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4 H227
Carc. 2 H351

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H227 - Combustible liquid
H351 - Suspected of causing cancer
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P308+P313 - If exposed or concerned: Get medical advice/attention
P370+P378 - In case of fire: Use ... to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

Alco Asphalt Roof Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Multi-constituent
Name : Alco Asphalt Roof Primer
CAS No : 8052-42-4

Name	Product identifier	%	GHS-US classification
EXXSOL D80, EXXONMOBIL	(CAS No) 64742-47-8	> 40	Flam. Liq. 4, H227 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Gently wash with plenty of soap and water.

First-aid measures after eye contact : In case of burns: Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.

First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : ON HEATING: Headache. Irritation of the respiratory tract. Nausea.

Symptoms/injuries after skin contact : ON HEATING: Burns.

Symptoms/injuries after eye contact : EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the eye tissue.

Symptoms/injuries after ingestion : No data available.

Chronic symptoms : No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Polyvalent foam. BC powder. Sand/earth. Carbon dioxide.

Unsuitable extinguishing media : Container may slop over if solid jet (water/foam) is applied.

5.2. Special hazards arising from the substance or mixture

Fire hazard : DIRECT FIRE HAZARD. Not easily combustible. INDIRECT FIRE HAZARD. Temperature above flashpoint: higher fire/explosion hazard.

Explosion hazard : DIRECT EXPLOSION HAZARD. No data available on direct explosion hazard. INDIRECT EXPLOSION HAZARD. No data available on indirect explosion hazard.

Reactivity : In molten state: reacts violently with water (moisture). On heating: formation of small quantities of hydrogen sulphide. Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters

Firefighting instructions : Cool tanks/drums with water spray/remove them into safety.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

Alco Asphalt Roof Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. See "Material-Handling" to select protective clothing.
- Emergency procedures : Mark the danger area. No naked flames. Wash contaminated clothes.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : If melted: allow liquid to solidify before taking it up. Start cleanup only if spill has cooled completely. Wash clothing and equipment after handling.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

7.2. Conditions for safe storage, including any incompatibilities

- Storage temperature : > 21 °C
- Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: heat sources.
- Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.
- Storage area : Keep container in a well-ventilated place. Fireproof storeroom. Meet the legal requirements.
- Special rules on packaging : SPECIAL REQUIREMENTS: closing. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
- Packaging materials : SUITABLE MATERIAL: No data available. MATERIAL TO AVOID: No data available.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Alco Asphalt Roof Primer (8052-42-4)

OSHA	Not applicable
------	----------------

EXXSOL D80, EXXONMOBIL (64742-47-8)

ACGIH	Not applicable
-------	----------------

OSHA	Not applicable
------	----------------

8.2. Exposure controls

- Materials for protective clothing : GIVE GOOD RESISTANCE: leather. viton. GIVE LESS RESISTANCE: neoprene. GIVE POOR RESISTANCE: butyl rubber. chlorosulfonated polyethylene.
- Hand protection : Gloves.
- Eye protection : Safety glasses.
- Skin and body protection : Heatproof clothing.
- Respiratory protection : On heating: Gas mask with filter type A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid

Alco Asphalt Roof Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless, Dark brown to black
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Characteristic odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 7.2
Solubility	: Water: Solubility in water of component(s) of the mixture : • EXXSOL D80, EXXONMOBIL: < 0.1 g/100ml • asphaltic bitumen, not cut back: insoluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

In molten state: reacts violently with water (moisture). On heating: formation of small quantities of hydrogen sulphide. Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Alco Asphalt Roof Primer (f)8052-42-4	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)

Alco Asphalt Roof Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Alco Asphalt Roof Primer (8052-42-4)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: ON HEATING: Headache. Irritation of the respiratory tract. Nausea.
Symptoms/injuries after skin contact	: ON HEATING: Burns.
Symptoms/injuries after eye contact	: EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the eye tissue.
Symptoms/injuries after ingestion	: No data available.
Chronic symptoms	: No effects known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - air : Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

Alco Asphalt Roof Primer (8052-42-4)

LC50 fishes 1	> 1000 mg/l (96 h; Pisces)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)

EXXSOL D80, EXXONMOBIL (64742-47-8)

EC50 Daphnia 1	> 10000 mg/l (Amphipoda)
----------------	--------------------------

12.2. Persistence and degradability

Alco Asphalt Roof Primer (8052-42-4)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

EXXSOL D80, EXXONMOBIL (64742-47-8)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

Alco Asphalt Roof Primer (8052-42-4)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

EXXSOL D80, EXXONMOBIL (64742-47-8)

Log Pow	> 3
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Recycle/reuse. Dissolve or mix with a combustible solvent. Remove to an authorized dump. Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery.
Additional information	: Can be considered as non hazardous waste according to Directive 2008/98/EC.

Alco Asphalt Roof Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT

Transport document description	: UN1999 Tars, liquid, 3, III
UN-No.(DOT)	: UN1999
Proper Shipping Name (DOT)	: Tars, liquid
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



Packing group (DOT)	: III - Minor Danger
---------------------	----------------------

Additional information

Other information	: No supplementary information available.
-------------------	---

ADR

Transport document description	: UN 3257 Elevated temperature liquid, n.o.s., 9, III, (D)
Packing group (ADR)	: III
Class (ADR)	: 9 - Miscellaneous dangerous substances and articles
Hazard identification number (Kemler No.)	: 99
Classification code (ADR)	: M9
Danger labels (ADR)	: 9 - Miscellaneous dangerous substances and articles



Tunnel restriction code (ADR)	: D
-------------------------------	-----

Transport by sea

UN-No. (IMDG)	: 3257
Class (IMDG)	: 9 - Miscellaneous dangerous substances and articles
EmS-No. (1)	: F-A
EmS-No. (2)	: S-P

Air transport

UN-No.(IATA)	: 3257
Class (IATA)	: 9 - Miscellaneous Dangerous Goods

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

Alco Asphalt Roof Primer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

SECTION 16: Other information

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H351	Suspected of causing cancer

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product