

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Alco Resurfacer Cold Process

CAS No : 8052-42-4
Product code : 205

Synonyms : asphalt / asphalt blending stocks: straight run residue / asphalt, not cut back / asphalt,

petroleum / asphalt, straight reduced / asphalt, straight run / asphalt, syriac / bitumen / bitumes, hot / carpeting medium / compact bitumen / earth pitch / Elevated temperature liquid, n.o.s. / Elevated temperature liquid, n.o.s., at or above 100 °C and below its flashpoint (including molten metals, molten salts, etc.), filled at a temperature higher than 190 °C / judean pitch / mineral pitch / petroleum asphalt / petroleum pitch / petroleum residue, alphalt / petroleum roofing tar / pitch, judean / residual asphalt / road asphalt / road binder / road tar / seal-coating

material

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive: component

Industrial use

1.3. Details of the supplier of the safety data sheet

ALCO PRODUCTS, LLC 580 St. Jean Detroit. MI 48214

T (313) 823-7500 - F (313) 331-4726

info@alco-products.com - www.alco-products.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 CHEMTREC

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Multi-constituent

Name : Alco Resurfacer Cold Process

CAS No : 8052-42-4

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

4.1. Description of first aid measures

First-aid measures general

: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

08/10/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact

: In case of burns: Wash immediately with lots of water (15 minutes)/shower. Do not tear off solidified product from the skin. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to

hospital.

First-aid measures after eye contact : In case of burns: Rinse immediately with plenty of water for 15 minutes. Do not apply

neutralizing agents. Take victim to an ophthalmologist.

First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce

vomiting. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical

service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : ON HEATING: Headache. Irritation of the respiratory tract. Nausea.

Symptoms/injuries after skin contact : ON HEATING: Burns.

Symptoms/injuries after eye contact : EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the eye tissue.

Symptoms/injuries after ingestion : No data available. Chronic symptoms : No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Polyvalent foam. BC powder. Sand/earth. Carbon dioxide.

Unsuitable extinguishing media : Container may slop over if solid jet (water/foam) is applied.

5.2. Special hazards arising from the substance or mixture

Fire hazard : DIRECT FIRE HAZARD. Not easily combustible. INDIRECT FIRE HAZARD. Temperature

above flashpoint: higher fire/explosion hazard.

Explosion hazard : DIRECT EXPLOSION HAZARD. No data available on direct explosion hazard. INDIRECT

EXPLOSION HAZARD. No data available on indirect explosion hazard.

Reactivity : In molten state: reacts violently with water (moisture). On heating: formation of small quantities of hydrogen sulphide. Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: seal off low-lying areas. Exposure to

fire/heat: have neighbourhood close doors and windows.

Firefighting instructions : Cool tanks/drums with water spray/remove them into safety.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. See

"Material-Handling" to select protective clothing.

Emergency procedures : Mark the danger area. No naked flames. Wash contaminated clothes.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.

Methods for cleaning up : If melted: allow liquid to solidify before taking it up. Start cleanup only if spill has cooled

completely. Wash clothing and equipment after handling.

6.4. Reference to other sections

No additional information available

08/10/2015 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep away from naked flames/heat. Observe strict hygiene. Keep

contaminated clothing. Reep away from naked flames/neat. Observe strict hygiene. Reep container tightly closed. Measure the concentration in the air regularly. Carry operations in the

open/under local exhaust/ventilation or with respiratory protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature : > 21 °C

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.

Storage area : Keep container in a well-ventilated place. Fireproof storeroom. Meet the legal requirements.

Special rules on packaging : SPECIAL REQUIREMENTS: closing. correctly labelled. meet the legal requirements. Secure

fragile packagings in solid containers.

Packaging materials : SUITABLE MATERIAL: No data available. MATERIAL TO AVOID: No data available.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Alco Resurfacer Cold Process (8052-42-4)		
ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m³
OSHA	Not applicable	

8.2. Exposure controls

Materials for protective clothing : GIVE GOOD RESISTANCE: leather. viton. GIVE LESS RESISTANCE: neoprene. GIVE POOR

RESISTANCE: butyl rubber. chlorosulfonated polyethylene.

Hand protection : Gloves.

Eye protection : Safety glasses.

Skin and body protection : Heatproof clothing.

Respiratory protection : On heating: Gas mask with filter type A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Solid.
Color : Dark brown to black

Odor : Characteristic odour
Odor threshold : No data available

pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : > 370 °C

Flash point : 204 - 288 °C

Auto-ignition temperature : 350 - 485 °C

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapor pressure : No data available

Relative vapor density at 20 °C : > 1
Relative density : > 1

Solubility : Insoluble in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in

chloroform. Soluble in tetrachloromethane. Soluble in carbondisulfide. Soluble in turpentine.

Log Pow : > 6 (Calculated)
Log Kow : No data available

08/10/2015 EN (English US) 3/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available
Viscosity, dynamic : > 0.17 Pa.s (135 °C)
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

Softening point : > 45 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

In molten state: reacts violently with water (moisture). On heating: formation of small quantities of hydrogen sulphide. Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Alco Resurfacer Cold Process (\f)8052-42-4		
LD50 oral rat	> 2000 mg/kg (Rat)	
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)	
Skin corrosion/irritation : Not classified		

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Alco Resurfacer Cold Process (8052-42-4)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : ON HEATING: Headache. Irritation of the respiratory tract. Nausea.

Symptoms/injuries after skin contact : ON HEATING: Burns.

Symptoms/injuries after eye contact : EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the eye tissue.

Symptoms/injuries after ingestion : No data available. Chronic symptoms : No effects known.

SECTION 12: Ecological information

		_			
1	2.1	- Т	oxi	CI	tv

Ecology - air : Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

Ecology - water : No water pollutant (surface water). Fouling to shoreline. Not harmful to fishes (LC50(96h)

>1000 mg/l). Not harmful to aquatic organisms.

08/10/2015 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Alco Resurfacer Cold Process (8052-42-4)		
LC50 fish 1	> 1000 mg/l (96 h; Pisces)	
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)	
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)	

12.2. Persistence and degradability

Alco Resurfacer Cold Process (8052-42-4)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

Alco Resurfacer Cold Process (8052-42-4)		
Log Pow	> 6 (Calculated)	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Recycle/reuse. Dissolve or mix with a combustible solvent. Remove to an authorized dump.

Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with

energy recovery.

Additional information : Can be considered as non hazardous waste according to Directive 2008/98/EC.

SECTION 14: Transport information

In accordance with DOT Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 3257, 9, III, (D)

Packing group (ADR) : III

Class (ADR) : 9 - Miscellaneous dangerous substances and articles

Hazard identification number (Kemler No.) : 99
Classification code (ADR) : M9

Hazard labels (ADR) : 9 - Miscellaneous dangerous compounds



Orange plates

99 3257

Tunnel restriction code (ADR) : D

Transport by sea

UN-No. (IMDG) : 3257

Class (IMDG) : 9 - Miscellaneous dangerous compounds

EmS-No. (1) : F-A EmS-No. (2) : S-P

08/10/2015 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

UN-No.(IATA) : 3257

Class (IATA) : 9 - Miscellaneous Dangerous Goods

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. **National regulations**

15.3. US State regulations

SECTION 16: Other information


NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

08/10/2015 EN (English US) 6/6